

Express Way, Whitwood  
Castleford  
West Yorkshire  
WF10 5QJ  
United Kingdom

Email:-  
mark.ward@tarmac.com  
Mobile Number:-  
07484036583

01924 896408

**Notes -**




Barrier To Be Used At All Road Closure points

**DETAIL B (B)**

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.  
Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.  
Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

- Notes:
- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
  - 2) 45° tapers have 1.5m spacing, no relaxations.
  - 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

**DETAIL C2 (C2)**



Single carriageway 40mph or less - 450mm traffic cones.  
Single/Dual carriageway 50mph or more - 750mm traffic cones.

- Notes:
- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

REV	DESCRIPTION	BY	DATE
/	.....	//	//

**Approval For Construction**

This drawing is deemed to be submitted for approval by the specified parties in accordance with the contract.  
Please confirm approval as soon as possible prior to the installation of the layout detailed on this drawing.  
If no negative comments and/or a rejection is received from the specified parties within the contracted period or prior to the proposed date of installation whichever is the soonest then the drawing will be deemed as approved.

**Edward Street Road Closure/Diversion**

**Traffic Management  
Diversion Routes**

Client <b>Ncc</b>			
Drawn by NW	Checked by TB	Submitted for approval Miles Howard	Authorised by .....
Date 02.08.18	Date 02.08.18	Date 02.08.18	Date .....
Contract No. J042168078/...		Scale NTS	
Drawing No. TTM/68078/.../02		Client Ref No. N/A	

